



Thumb Screw for ASFA L and S worm-drive clamps

Worm-drive clamps can be fitted relatively tightly, easily and quickly using this Thumb Screw, without the need for tools. Once the clamp has been tightened, the thumb screw can be removed. Manufactured in durable red plastic.

Application Ø	Width Screw (mm)	Part n°	Box Quantity (M00)	Outer Packing
All Ø available ASFA L and S	7	0217046-1	100	1.000



Safety Cap for ASFA L and S worm-drive clamps

These Safety Caps for worm-drive hose clamps are a practical and quickly assembled solution which prevent injuries by protecting the band end. They are manufactured in two different colours which help to determine the material quality of the clamps: (Red: W1 and W2 - Blue: W3, W4 and W5).

Bandwidth	Part n°	Colour	Box Quantity (M00)	Outer Packing
9 mm (L)	0217040-1	RED	100	1.000
9 mm (L)	0217041-1	BLUE	100	1.000
12 mm (S)	0217044-1	RED	100	1.000
12 mm (S)	0217045-1	BLUE	100	1.000



Safety Collar for ASFA L and S worm-drive clamps

The Safety Collar is an ideal solution which prevents the screwdriver from slipping out of the slot in the screw while tightening. It is easy to assemble and extremely useful. The slot is easily accessible while the collar helps to hold the screwdriver in place. Available in two colours, red and blue, which help to identify the material quality of the clamp: (Red: W1 and W2 - Blue: W3, W4 and W5).

Application Ø	Part n°	Colour	Box Quantity (M00)	Outer Packing
All Ø available ASFA L and S	0217037-1	RED	100	1.000
All Ø available ASFA L and S	0217038-0	BLUE	100	1.000